10

CLAIMS

- 1. A skateboard with vibration-absorbing function, comprising
- a platform,

coupling stage.

- a coupling stage formed on bottom center of the platform;
- 5 two swing members connected to two distal ends of the coupling stage;
 - at least two resilient members arranged between the coupling stage and the swing members;
 - at least two wheels, each arranged below the swing member and corresponding to the resilient member.
 - The skateboard with vibration-absorbing function as in claim
 wherein one swing member has a braking section on rear end
 thereof.
- 3. The skateboard with vibration-absorbing function as in claim
 15 1, wherein the swing member has a retaining rod extended toward the coupling stage and clamped by a confining section arranged in the
- The skateboard with vibration-absorbing function as in claim
 , wherein a plurality of supporters are embedded into the platform
 to reinforce the mechanical structure of the platform.

10

- The skateboard with vibration-absorbing function as in claim
 wherein the resilient member is covered with a flexible dust cover.
 - A skateboard with vibration-absorbing function, comprising a platform,
- 5 a coupling stage formed on bottom center of the platform;
 - a flexible swing plate connected to the coupling stage;
 - two wheels arranged below the flexible swing plate.
 - The skateboard with vibration-absorbing function as in claim 6, wherein the flexible swing plate has a braking section on rear end thereof.
 - 8. The skateboard with vibration-absorbing function as in claim 6, wherein the flexible swing plate is formed by composite stacking plates.
- The skateboard with vibration-absorbing function as in claim
 1, wherein the platform has two crossing and elongated coupling plates below and the coupling plates are pivotally connected to the platform.
 - 10. The skateboard with vibration-absorbing function as in claim 1, wherein the swing members are two inner swing members.
- 20 11. The skateboard with vibration-absorbing function as in

claim 1, wherein the resilient member is an air sac.

12. The skateboard with vibration-absorbing function as in claim 1, wherein the braking section is a base with a rotor.